

IS 30-50 IDR. ORIZ.

insaccatrici orizzontali

hydraulic sausage stuffers



IS 30 IDR. ORIZ.

- Macchine insaccatrici di semplice concezione, ma realizzate con materiali e accorgimenti di alta qualità.
- Robusta struttura realizzata in acciaio inox.
- Macchina completamente lavabile mediante spruzzo d'acqua.
- Cilindro in acciaio inox AISI 304 conforme alle recenti norme igienico sanitarie raggiato e senza resto di saldatura interna, per consentire una semplice pulizia.
- Completamente a norme antinfortunistiche con protezione sul cilindro e comando a pedale a bassa tensione.
- Pistoni provvisti di valvole per lo sfiato dell'aria.
- Avanzamento pistone regolabile mediante un pomello.
- Ritorno pistone sempre a velocità massima.
- Completa di imbuto in polietilene di tre differenti misure.

Opzionali:

- Imbuti inox.


- Machines of simple design, but manufactured with high quality materials and details.
- Strong structure made of stainless steel.
- Completely cleanable by means of a water sprinkle.
- Stainless steel AISI 304 cylinder standing to the newest sanitary-hygienic norms, with no edge inside of it and no weld rests, to simplify the cleaning.
- Completely realized standing to the most up to date accidental prevention norms, with protection on cylinder and low tension treadle drive.
- Pistons provided with air exhaust valve.
- Forward feeding adjustable by means of knob.
- Backward feeding always at highest speed.
- Complete with three polyethylene funnels of different sizes.

Optional:

- Stainless steel funnels.

Cilindro CE
Cylinder CE

IS 50 IDR. ORIZ.

Ribaltamento cilindro
Cylinder overturnProtezione cilindro e valvole sfiato
aria tampone
Cylinder protection and pad exhaust
valves

	watt/Hp	lt	mm	ø mm	mm					mm	mm	mm	mm	mm	mm	mm	kg	mm	kg
IS 30 Idr. Oriz.	560/0.75	30	600	260	640	4"10"	60"	30"	10-18-25	360	1605	440	1010	400	720	1100	111	1620x500x500	120
IS 50 Idr. Oriz.	560/0.75	50	600	320	650	5"40"	60"	30"	10-18-25	420	1650	-	-	430	-	-	153	1620x500x500	174