



Industria 4.0

# KATANA 6 - 12 - 20

## cutter orizzontali horizontal cutter

- Completamente realizzato in acciaio inox AISI 304
- Lame guidate da potente motore asincrono ventilato
- Robusta vasca in acciaio inox AISI 304, smontabile
- Coperchio in acciaio inox, con calotta in Kepital alimentare ad alta resistenza
- Coperchio interbloccato facilmente smontabile per agevolarne pulizia e sanificazione
- Comandi con pulsanti inox IP 67
- Mozzo con 3 lame di serie facilmente rimovibile (configurabile a 2 lame)
- Disponibili mozzi lame specifici per lavorazioni particolari
- Massima protezione infiltrazione liquidi sull'albero
- Ideali per carni, pesce e verdure ma adatto anche a molteplici altre lavorazioni

### Opzioni:

- Piedini regolabili
- Gambe inox con ruote e freno
- Mozzi con lame non affilate, dentate o smussate

### MODELLO 12 PTO

- PTO: presa di forza per accessori opzionali con attacco standard 12 come TC, TV (solo non CE)

### MODELLO 12-20 VV

- Variatore di velocità continuo gestito da inverter
- Motore trifase alimentato monofase
- Motoriduttore vasca indipendente

- *Completely made in AISI 304 stainless steel*
- *Blade driven by powerful ventilated asynchronous motor*
- *Sturdy, removable AISI 304 stainless steel bowl*
- *Stainless steel lid with high resistance hood in Kepital*
- *Easily removable interlocking lid to facilitate cleaning and sanitising*
- *Controls with IP 67 stainless steel buttons*
- *Easily removable blade hub with 3 blades standard (configurable to 2 blades)*
- *Dedicated knives available for special purposes*
- *Maximum protection against liquid infiltration on the shaft*
- *Perfect for meat, fish and vegetables, but also suitable for many other types of processing*

### Options:

- *Adjustable feet*
- *Stainless steel legs with wheels and lock*
- *Hub with blunted, serrated or unsharpened blades*

### MODEL 12 PTO

- *PTO: Power Traction Outlet for optional accessories with 12 standard connection like TC, TV (only non CE)*

### MODEL 12-20 VV

- *Continuous speed control controlled by inverter*
- *Three-phase motor power supply single-phase*
- *Gearmotor freestanding tub*



KATANA 20 VV



KATANA 12 VV



KATANA 6

### MODELLO EL

- Versione con controllo elettronico touch avanzato
- Permette di impostare 8 programmi personali con diverse fasi di velocità e tempo
- Chip WiFi integrato che permette un utilizzo e una gestione ottimale anche da remoto tramite il portale SRCS
- Pratica APP di controllo gratuita per la gestione dei programmi e dei log di lavorazione
- Industry 4.0 ready

### MODEL EL

- *Touch control advanced version*
- *It allows you to set 8 personal programs with different speed and time phases*
- *Integrated WiFi chip allows optimal use and management even remotely via the SRCS portal*
- *User friendly free control APP for the management of programs and processing logs*

## Standard



Mozzo a 3 lame  
Hub with 3 blades



Termometro su coperchio  
Thermometer on lid



KATANA EL

## Optionals



Mozzo a 3 lame dentate  
Hub with 3 serrated blades







Mozzo a 3 lame non affilate  
Hub with 3 unsharpened blades



Mozzo a 3 lame smussate  
Hub with 3 smooth edge



KATANA 12 PTO



					A	B	C	D	E	F	G	H	L	M	N	O	P	Q	R			
	watt/Hp		lt	r.p.m.	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm	kg
<b>Katana 6</b>	370/0.5	1ph/3ph	6	1440	297	540	356	714	516	832	582	25	407	695	428	776	710	864	1089	60	1200x670x800	79.5
<b>Katana 12</b>	1ph 750/1 - 3ph 1.500/2	1ph/3ph	12	1440	335	600	393	758	587	902	680	25	443	785	467	836	710	873	1138	75	1200x670x800	89.5
<b>Katana 12 VV</b>	1.610/2.2	1ph	12	600/2.600	335	600	393	758	587	902	680	25	443	785	467	836	710	873	1138	75	1200x670x800	89.5
<b>Katana 12 PTO</b>	1ph 750/1 - 3ph 1.500/2	1ph/3ph	12	1440	335	600	393	758	587	902	680	25	443	785	467	836	710	873	1138	75	1200x670x800	89.5
<b>Katana 20 VV</b>	2.387/3.25	1ph	20	600/2.600	390	650	450	820	700	1013	822	25	507	945	521	886	710	883	1189	92	1000x1200x800	111.5